

High Accuracy Thermometer Type MI-8822


RTD Thermometer

- Rigid housing design and the most accurate pt100 probe
- High temperature accuracy $\pm 0.15^{\circ}\text{C}$ & 0.01°C resolution
- Complete set IP67 waterproof and washable in washing machine
- Follow HACCP principle to check food safety
- Green/Red dual color backlight to indicate temp. hazards
- Countdown timer function included
- Hold function to freeze current reading
- One touch to display temperature change from baseline
- Temperature unit $^{\circ}\text{C}/^{\circ}\text{F}$ switchable
- No sleep mode function available
- Super big LCD for easy reading
- Max./Min./Avg. reading display
- Temp. high alarm threshold programmable
- 99 points data records with review




MI-8822

Safe, Quick and Easy to measure temperature precisely!!
Follow **HACCP** principle, Green/Red backlight to indicate temp. Hazards!



Measured temp: 4~60°C



Measured temp: $<4^{\circ}\text{C}$ or $>60^{\circ}\text{C}$



PT100 PENETRATE PROBE
TEMP. RANGE: $-100\sim 300^{\circ}\text{C}$
LENGTH: 150MM
DIAMETER: 6.0MM
HANDLE LENGTH: 100MM
CABLE LENGTH: 1100MM



STAINLESS PROBE HOLDER
INCLUDED IN STANDARD
PACKAGE TO OFFER YOU
STEADY PROBE SUPPORT

Custom made RTD probes are available upon request.

Technical Specifications

Model	MI-8822
Measuring range	-100.00~300.00°C (-148.00~572.00°F)
Resolution	0.01°C/0.01°C
Accuracy	+/-0.15°C
IP rating	IP67
Temp. Response time	3 min typical
LCD update time	every second
LCD size (mm, HxW)	54x32.5
Probe size (mm)	
Length	150
Diameter	3.2
Handle length (mm)	100
Cable length (mm)	1100
Probe Weight	~50g
Operating temp.	10~35°C
Operating RH%	Hummidity < 80%
Storage temp.	-20~50°C
Storage RH%	Hummidity < 90%
Dimensions (mm, LxWxT)	169x78.3x34.4
Weight	~200g
Battery	6pcs AAA battery
Standard Package	Meter, RTD probe, stainless holder, battery, manual
Optional Accessory	Custom made RTD probes are available upon request

